

Viral Plugin Guide

Loading the Plugin

Loading Plugins into your JW Player is easy. If you're using JW Player 4.3 or above, then it will automatically load Plugins from LongTail's CDN based on simple settings in your HTML embed code. Just set your 'plugins' flashvar to include 'viral-2'.

Flashvar: `plugins = viral-2`

Plugin Configuration

This plugin supports additional configuration options via flashvars.

Flashvar: `viral.onpause = true | false`

This flashvar is used to specify whether or not if the Viral options appear on pause.

The values determine behavior as follows:

- `true` - options appear on video pause
- `false` - options do not appear on video pause

Flashvar: `viral.oncomplete = true | false`

This flashvar is used to specify whether or not if the Viral options appear when the playback completes.

The values determine behavior as follows:

- `true` - options appear on playback completion
- `false` - options do not appear on playback completion

Flashvar: `viral.allowmenu = true | false`

Variable to control the menu button in the control bar:

- `true` - Menu button appears in the control bar (default)
- `false` - Menu button doesn't appear in the control bar

Viral Plugin Guide

Flashvar: `viral.functions = embed,link,recommendations | all`

This flashvar is used to specify which of the Viral options to include in the options panel. One or more individual options can be specified in a comma-delimited list

The values determine behavior as follows:

- `embed` - include the embed option

- `link` - include the link option

- `recommendations` - include list of recommendations

Flashvar: `viral.recommendations = URL`

This flashvar is used to specify a URL to an XML file with mRSS-formatted recommendations.

A sample recommendations file can be found at:
<http://www.jeroenwijering.com/upload/mrss.xml>

Flashvar: `viral.link = URL`

This flashvar is used to specify the URL to be displayed to the user in the link field. This URL should reference the current page being viewed.

Flashvar: `viral.email_subject = text`

This flashvar is used to specify the text to show in the subject line of the email sent from this plugin - the default is "Check out this video!"

Flashvar: `viral.email_footer = text`

This flashvar is used to specify the text to show in the footer of the email sent from this plugin - the default is a link to www.longtailvideo.com

Flashvar: `viral.embed = URL`

This flashvar is used to specify the embed code to be displayed to the user in the embed field. This code should reference the current page being viewed. Note: The embed code needs to be escaped and, due to technical limitations, cannot be re-embedded.

Viral Plugin Guide

Flashvar: `viral.matchplayercolors = true | false`

This flashvar is used to specify if the plugin should match the colors used by the regular player.

This will override the `fgcolor` and `bgcolor` flashvars if set to true:

- true - Match player colors (default)

- false - Don't match player colors

Flashvar: `viral.fgcolor 0xFFFFFF`

Foreground color of the plugin

Flashvar: `viral.bgcolor = 0x333333`

Background color of the plugin

Additional Information

The following Flash parameters have to be set correctly in order for the Viral plugin to work properly.

Flash Param: `allowscriptaccess = always`

Configures Flash to allow scripting access.

Flash Param: `allownetworking = all`

Configures Flash to allow networking API access.